

BRE



**TENSILE MEMBRANE ACTION AND ROBUSTNESS
OF STRUCTURAL STEEL JOINTS UNDER NATURAL FIRE
EC FP5 HPRI – CV 5535**

**Cardington Fire Test
January 16. 2003**


David Moore, František Wald, Aldina Santiago
BRE Watford, CTU in Prague, Coimbra University

Contents



- **Cardington Laboratory**
- **Structural Integrity Test**
- **Preparation**
- **Temperatures**
- **Connections**
- **Composite slab**
- **Conclusion**





Cardington, Hangar





Experimental area 48 m x 65 m x 250 m

Timber structure - 6 floor



Concrete structure - 7 floor



Steel composite structure

Erected 1993

Eight floors

Plan area - 945 m²

Steel braced frame

Connections:

beam-column connections:

flexible end plates

beam-beam connections:

fin plates






Typical composite structure

Contenta

- Cardington Laboratory
- ▪ Structural Integrity Test
- Preparation
- Temperatures
- Connections
- Composite slab
- Conclusion



Fire experiments



Summary of fire tests

Test	Description	Fire compartment		Loading	
		size, m	area, m ²	Fire	Mech. G + % Q
1	One beam	8 x 3	24	Gas	30%
2	One frame	21 x 2,5	53	Gas	30%
3	Corner comp.	10 x 7	70	45 kgm ⁻²	30%
4	Corner comp.	9 x 6	54	45 kgm ⁻²	30%
5	Large comp.	21 x 18	342	40 kgm ⁻²	30%
6	Office	18 x 9	136	46 kgm ⁻²	30%
7	Integrity	11 x 7	77	40 kgm ⁻²	56%

Summary of duration, temp and deformations

Test	Org.	Level	Duration (mins).	Temperatures, °C		Deformation, mm	
				atmos	steel	maximal	residual
1	BS	7	170	913	875	232	113
2	BS	4	125	820	800	445	265
3	BS	2	75	1020	950	325	425
4	BRE	3	114	1000	903	269	160
5	BRE	3	70		691	557	481
6	BS	2	40	1150	1060	610	-
7	ČVUT	4	55	1108	1088	~1200	925



Test 2 – BS, 1996 – Column shortening



Structural Integrity Test January, 16. 2003

Project team

Mr. Martin Beneš	Research Student, CTU Prague
Mr. Luis Borges	Research Student, University Coimbra
Mrs. Petra Hřebíková	Research Student, CTU Prague
Mrs. Magdaléna Chladná	Research Student, Slovak Technical University, Bratislava
Mr. David Jennings	Engineering Technician, BRE Watford
Mr. Tom Lennon	Supervising Engineer, BRE Watford
Dr. David Moore	Project Director, BRE Watford
Mrs. Aldina Santiago	Research Student, University Coimbra
Prof. Luis S. da Silva	Research Group Member, University Coimbra
Mr. Paul Sims	Project Manager, BRE Watford
Dr. Zdeněk Sokol	Research Group Member, CTU Prague
Dr. Jan Pašek	Research Group Member, CTU Prague
Mr. Nick Petty	Contracted Technicians, BRE Watford
Mr. Jiří Svoboda	Res. Group Member, TMV SS, Prague
Prof. Frantisek Wald	European Research Group Leader, Prague
Mr. David White	Project Leader , BRE Watford

Research Project

**Tensile membrane action
and robustness of structural steel joints under natural fire**

EC FP5 HPRI - CV 5535

Participating Institutions

Building Research Establishment

Czech Technical University in Prague

Coimbra University,

Technical University, Bratislava

Objectives

To determine the:-

- ◆ Temperatures in elements and joints
- ◆ Internal forces in the connections
- ◆ Behaviour of the composite Slab



Contents

- Cardington Laboratory
- Structural Integrity Test
- ➔ ■ Preparation
- Temperatures
- Connections
- Composite slab
- Conclusion



Fire Compartment




Wall

3 layers of gypsum plasterboard
(15 mm + 12,5 mm + 15 mm)
with $K = 0,19 - 0,24 \text{ W/mK}$

Window

9 m x 1,27 m

Protected Members



Columns

External joints


1 m of the primary beam

15 mm of Cafco300 vermiculite-cement spray

$K = 0,078 \text{ W/mK}$

Mechanical Load

- ◆ Permanent 100%
 - ◆ Variable permanent 100%
 - ◆ Live 56%
- by sand bags



Fire Load




Timber cribs 50 x 50 mm - fire load 40 kg/m²





16 1 2003

Instrumentation

- ◆ 148 thermocouples
- ◆ 57 strain gauges





◆ 37 deformations

- ◆ 10 video cameras
- ◆ 2 thermo cameras














Contents

- Cardington Laboratory
- Structural Integrity Test
- Preparation
- Temperatures
- Connections
- Composite slab
- Conclusion




Temperatures



Gas 1108 °C in 55 min. (predicted 1078 °C in 53 min.)


Beam 1088 °C in 57min. (predicted 1067 °C in 54 min.)

Temperature profiles







Heating



Thermo-cameras







Cooling

























BRE











980,0°C



800

600



400

400,0°C



BRE







BRE



BRE







980,0°C



800




600




400

400,0°C



BRE








BRE







980,0°C




800



600



400



400,0°C











980,0°C







800



600


400

400,0°C










980,0°C

800

600

400

400,0°C






980,0°C



800



600



400


400,0°C













980,0°C



800


600

400



400,0°C








BRE






Contents




- Cardington Laboratory
- Structural Integrity Test
- Preparation
- Temperatures
-  Connections
- Composite slab
- Conclusion



Fin Plate Temperature Profile






Header Plate Temperature Profile





- Thermocouples (TC)
- TC + HSG in Bolt
- HT Strain Gauges (HSG)

Header Plate Strain Gages




- Thermocouples (TC)
- TC + HSG in Bolt
- HT Strain Gauges (HSG)


Local Buckling of Beam Lower Flanges



Fracture of End-Plates




Ovalization of holes in the web beam in the fin plate joints



Column Flange Buckling



Beam Web Shear Zones




Contents

- Cardington Laboratory
- Structural Integrity Test
- Preparation
- Temperatures
- Connections
- Composite slab
- Conclusion




Concrete slab cracking



Concrete slab deformation

Slab deflection after test
Date: 23th January 2003



Residual deformation max 925 mm

Conclusions

- Fracture of end plates
- Elongation of holes in fin plates
- Integrity of composite slab
- Collapse of structure not reached
 - Mechanical load 56%
 - Fire load 40 kg/m²

Thank you for your attention

